

EIL 7 Premium

MINI INSTANTANEOUS WATER HEATERS

PRODUCT-NO.: 200137

Enjoy hot water without any detours Compact convenience that speaks for itself. Your preferred temperature without the annoyance of heat loss from the pipework along the way – this mini instantaneous water heater brings you the "new normal". The appliance with electronic closed-loop control is especially well suited to hand washbasins, where it will supply you with small amounts of warm water.

The main features

Mini instantaneous water heater with electronic closed-loop control for small amounts of hot water available immediately

Flexible installation thanks to undersink or oversink installation

Can be operated with pressure-tested or non-pressurised taps

Accurate temperature delivery up to the maximum output

Temperature limit adjustable from approx. 30 °C to 50 °C

Special aerator for perfect flow pattern



EIL 3 Premium

Product-No.: 200134



EIL 4 Premium

Product-No.: 200135



EIL 6 Premium

Product-No.: 200136



| Type | EIL 3 Premium | EIL 4 Premium | EIL 6 Premium |
|----------|---------------|---------------|---------------|
| Part no. | 200134 | 200135 | 200136 |

Technical data

| | | | |
|--|--------------------------|--------------------------|--------------------------|
| Rated voltage | 230 V | 230 V | 230 V |
| Rated voltage 1 | 200 V | 200 V | 200 V |
| Rated voltage 2 | 220 V | 220 V | 220 V |
| Rated output | 3,53 kW | 4,4 kW | 5,7 kW |
| Rated output 1 | 2,7 kW | 3,3 kW | 4,3 kW |
| Rated output 2 | 3,2 kW | 4,0 kW | 5,2 kW |
| Rated current | 15,2 A | 19,1 A | 24,7 A |
| Rated current 1 | 13,3 A | 16,7 A | 21,6 A |
| Rated current 2 | 14,5 A | 18,2 A | 23,6 A |
| Fuse protection | 16 A | 20 A | 25 A |
| Fuse protection 1 | 16 A | 20 A | 25 A |
| Fuse protection 2 | 16 A | 20 A | 25 A |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| Frequency 1 | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| Frequency 2 | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| Phases | 1/N/PE | 1/N/PE | 1/N/PE |
| Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$) | 1000 $\mu\text{S/cm}$ | 1000 $\mu\text{S/cm}$ | 1000 $\mu\text{S/cm}$ |
| Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$) | 770 $\mu\text{S/cm}$ | 770 $\mu\text{S/cm}$ | 770 $\mu\text{S/cm}$ |
| Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$) | 1000 $\Omega \text{ cm}$ | 1000 $\Omega \text{ cm}$ | 1000 $\Omega \text{ cm}$ |
| Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$) | 1300 $\Omega \text{ cm}$ | 1300 $\Omega \text{ cm}$ | 1300 $\Omega \text{ cm}$ |
| Height | 143 mm | 143 mm | 143 mm |

| | | | |
|----------------------------------|------------|------------|------------|
| Width | 190 mm | 190 mm | 190 mm |
| Depth | 82 mm | 82 mm | 82 mm |
| Switch-on water flow rate | >1,5 l/min | >1.8 l/min | >2,2 l/min |
| IP rating | IP25 | IP25 | IP25 |
| Temperature setting | 30 - 50 °C | 30 - 50 °C | 30 - 50 °C |
| Colour | white | white | white |
| Weight | 1.50 kg | 1.50 kg | 1.50 kg |
| Energy efficiency class (A+ → F) | A | A | A |



| | |
|----------|---------------|
| Type | EIL 7 Premium |
| Part no. | 200137 |

Technical data

| | |
|--|--------------------------|
| Rated voltage | 400 V |
| Rated voltage 1 | 380 V |
| Rated voltage 2 | 400 V |
| Rated output | 6,5 kW |
| Rated output 1 | 5,9 kW |
| Rated output 2 | 6,5 kW |
| Rated current | 16,3 A |
| Rated current 1 | 15,5 A |
| Rated current 2 | 16,3 A |
| Fuse protection | 20 A |
| Fuse protection 1 | 16 A |
| Fuse protection 2 | 20 A |
| Frequency | 50/- Hz |
| Frequency 1 | 50/- Hz |
| Frequency 2 | 50/- Hz |
| Phases | 2/PE |
| Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$) | 1000 $\mu\text{S/cm}$ |
| Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$) | 770 $\mu\text{S/cm}$ |
| Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$) | 1000 $\Omega \text{ cm}$ |
| Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$) | 1300 $\Omega \text{ cm}$ |
| Height | 143 mm |

| | |
|----------------------------------|------------|
| Width | 190 mm |
| Depth | 82 mm |
| Switch-on water flow rate | >2.2 l/min |
| IP rating | IP25 |
| Temperature setting | 30 - 50 °C |
| Colour | white |
| Weight | 1.50 kg |
| Energy efficiency class (A+ → F) | A |

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.